



Score-8 Set

Plug & Play Satellitensystem

- 1 x HDSP-6 Amplifier
- 2 x Score-8
- 2 x Transport & rain cover for Score-8
- 4 x Paveosub-118 with detachable front-wheel board, transport & rain cover
- 2 x M20 rod with »Ring Lock«
- 4 x Cable clamps
- 1 x Carrying bag for 2 x telescopic distance rods
- 4 x 10 m, 2 x 3 m Speakon cable (4 x 4 qmm)

Score-8sp Set

Plug & Play Satellitensystem self-powered

- 2 x Score-8
- 2 x Transport & rain cover for Score-8
- 2 x Paveosub-118 with detachable front-wheel board, transport & rain cover
- 2 x Paveosub-118sp with detachable front-wheel board, transport & rain cover
- 2 x M20 rod with »Ring Lock«
- 4 x Cable clamps
- 1 x Carrying bag for 2 x telescopic distance rods
- 4 x 3 m Speakon cable (4 x 4 qmm)

The Score-8 Set is 'Plug and Play'. All components are matched, adjusted and limited via the integrated speaker management system (DSP). The sound is synchronised right away, without having to make further adjustments. The possibility of splitting, extension, scaling, ease of use and comprehensive, well thought out accessories complete the Score-8 Set and make it a universal PA tool with a very wide range of applications.

HDSP-6

Quantity channel	3 CH, class-D latest generation
Power output 4 Ω	8.000 W (2 x 2.400 W + 4 x 800 W)
Dimensions/Weight	19" x 2HE x 470 mm / 9,7 kg

Score-8

Frequency range	65 Hz - 19 kHz (- 10 dB) 78 Hz - 17,3 kHz (+/- 3 dB)
Coverage range	90° x 40° oder 60° x 40°
Power handling 4 Ω	500 W AES / 1.000 W program / 2.000 W peak
Sound pressure	130 dB SPL AES / 133 dB SPL program / 136 dB SPL peak
Components	2 x 8" Neodym LF with 2,5" voice coil 1 x 1,4" Neodym HF with 2,4" voice coil
Dimensions/Weight	625 (h) x 262 (w) x 337 mm (d) / 19,6 kg

Paveosub-118/118sp

Lower cut-off frequency	33 Hz (- 10 dB) 39 Hz (- 3 dB)
Coverage range	Omnidirektional
Power handling 8 Ω	1.200 W AES / 2.400 W program / 4.800 W peak
Sound pressure	131 dB SPL AES / 134 dB SPL program / 137 dB SPL peak
Components	1 x 18" Neodym long excursion woofer (LF) with 4" voice coil
Dimensions/Weight	540 (h) x 540 (w) x 4740 mm (d) / 41 kg (self-powered: 45,8 kg)
Amplifier	3-channel 4 kW
Power output CH1 LF	2.400 W/4 Ω, 1.580 W/8 Ω, 800 W/16 Ω
Power output CH2 & CH3	800 W/4 Ω, 450 W/8 Ω, 200 W/16 Ω

