

Aleasub-10

















The Aleasub-10 is a subwoofer specifically designed as low frequency extension of our successful Alea-4. It serves all media and installation needs with its discreet yet classy modern design and satisfies even increased demand for optical appearance. Small size goes hand in hand with high efficiency, a powerful low end and very precise sound reproduction. Size and appearance allow it to blend into any location.

The 10" woofer with latest generation highpower 3" voice coil has a moisture resistant coating. Connectivity is take care of by two Neutrik Speakon and a 4-pole Phoenix Contact connector.

Due to their uniform design all Alea speakers offer the same creative potential. Like Alea-4 also the Alea-10 can be custom designed with all RAL and effect colours, as well as bi- or triple-coloured. A different colour can be designated to cabinet, micromesh honeycomb grille and ornamental ring.

Grille and ornamental ring can also be coated in gold or chrome. This way it's even possible to adapt the Aleasub-10 to your own CI needs.

There is an optional heavy-duty bracket to mount the system on ceilings or truss. Like Alea-4 we offer a concealed and elegant wall mount. The back plate is recessed into the cabinet leaving space for a shallow wall mount and Phoenix Contact connectors.

For mobile use an optional handle can be attached to the back plate and rubber feet (included) fixed to positions indicated at the bottom of the cabinet.

All of these technical and visual features turn Aleasub-10 into a professional versatile tool to implement your requirements. Together with Alea-4 mid-high speakers it forms a compact and visually pleasing mini PA.









Lower cut-off frequency 39 Hz (- 10 dB) 49 Hz (- 3 dB)

Coverage range Omnidirektional

Power handling 8 \Omega 350 W AES / 700 W program / 1.400 W peak

Sound pressure 117 dB SPL AES / 120 dB SPL program / 123 dB SPL peak

Components 1 x 10" Ferrit Chassis with 3" voice coil

Connectors 2 x Neutrik NL4 Speakon IN/OUT (loop through), configuration: 2+/2-

1 x Phoenix contact terminal, 4 pole split into 2 x IN/OUT

Mounting 3 x M10 mounting point on the side walls

1 x M20 pole mount

Swivel bracket with raster for wall, ceiling, floor mounting

or mounting on truss means of a clamp

Handle can be attached to the back plate (optional)

Retractable mechanism for concealed wall, ceiling mount in the back side

Dimensions/Weight 363 (h) x 306 (w) x 400 mm (d) / 17,3 kg