



Score-5 Set

Plug & Play Satellitensystem

- 1 x HDSP-3 Amplifier
- 2 x Score-5
- 2 x L-bracket Set for Score-5
- 1 x Carrying bag for up to 2 x Score-5
- 2 x Paveosub-112 with detachable front-wheel board, transport & rain cover
- 2 x M20 rod with »Ring Lock«
- 4 x Cable clamps
- 1 x Carrying bag for 2 x telescopic distance rods
- 2 x 10 m, 2 x 3 m Speakon cable (4 x 4 qmm)

Score-5sp Set

Plug & Play Satellitensystem self-powered

- 2 x Score-5
- 2 x L-bracket Set for Score-5
- 1 x Carrying bag for up to 2 x Score-5
- 1 x Paveosub-112 with detachable front-wheel board, transport & rain cover
- 1 x Paveosub-112sp with detachable front-wheel board, transport & rain cover
- 2 x M20 rod with »Ring Lock«
- 4 x Cable clamps
- 1 x Carrying bag for 2 x telescopic distance rods
- 1 x 10 m, 2 x 3 m Speakon cable (4 x 4 qmm)

The Score-5 Set is 'Plug and Play'. All components are matched, adjusted and limited via the integrated speaker management system (DSP). The sound is synchronised right away, without having to make further adjustments.

The possibility of splitting, extension, scaling, ease of use and comprehensive, well thought out accessories complete the Score-5 Set and make it a universal PA tool with a very wide range of applications.

HDSP-3

Quantity channel	3 CH, class-D latest generation
Power output 4 Ω	4.000 W (1 x 2.400 W + 2 x 800 W)
Dimensions/Weight	19" x 2HE x 470 mm / 7 kg

Score-5

Frequency range	71 Hz - 19 kHz (- 10 dB) 139 Hz - 15,7 kHz (+/- 3 dB)
Coverage range	70° horizontal, 55° vertical
Power handling 12 Ω	200 W AES / 400 W program / 800 W peak
Sound pressure	114 dB SPL AES / 117 dB SPL program / 120 dB SPL peak
Components	2 x 5" Neodym LF with 32 mm (1,25") voice coil 1 x 1" Ferrit compression driver with 1" voice coil
Dimensions/Weight	450,5 (h) x 172 (w) x 190 mm (d) / 6,1 kg

Paveosub-112/112sp

Lower cut-off frequency	35 Hz (- 10 dB) 41 Hz (- 3 dB)
Coverage range	Omnidirektional
Power handling 8 Ω	1.000 W AES / 2.000 W program / 4.000 W peak
Sound pressure	129 dB SPL AES / 131 dB SPL program / 134 dB SPL peak
Components	1 x 12" Neodym long excursion woofer (LF) with 4" voice coil
Dimensions/Weight	300 (h) x 520 (w) x 485 mm (d) / 23,1 kg (self-powered: 28,8 kg)
Amplifier Paveosub-112sp	3-channel 4 kW
Power output CH1 LF	2.400 W/4 Ω, 1.580 W/8 Ω, 800 W/16 Ω
Power output CH2 & CH3	800 W/4 Ω, 450 W/8 Ω, 200 W/16 Ω

